

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APP. NO. 09/485,443

B¹
connecting a non-used port of the node of the lowest priority with a port of the node of the next priority; and

repeating the connecting step until all of said nodes are connected together, whereby said nodes are connected through said communication ports according to priority order.

Sub
SCI 3
B²
(Twice Amended) A method of optimizing a topology of a serial bus having a plurality of nodes each with communication ports, comprising the steps of:

comparing a total number of ports of all of said nodes with a reference value varying with the number (N) of said nodes to determine whether a prerequisite for constructing said topology is satisfied, the prerequisite being that the total number of ports of all of said ports is not less than $2(N-1)$;

prioritizing said nodes according to the number of said communication ports and a transmission speed of said nodes when said prerequisite is satisfied, such that nodes of higher speed have higher priority than nodes of lower speed and nodes of equal speed are prioritized so that nodes having more of said communication ports have a higher priority than nodes having fewer of said communication ports;

connecting a non-used port of the node of the lowest priority with a port of the node of a next higher priority;

repeating the connecting step until all of said nodes are connected together; and

separating the last connected node to assign to the node of the foremost priority among nodes in a next higher speed group than the separated last connected node when no port remains

AMENDMENT UNDER 37 C.F.R. § 1.111
U.S. APP. NO. 09/485,443

32
in the node of the lowest priority to connect with the node of next priority during the repeating step, whereby said nodes are connected through said communication ports according to priority order.
